

# CANopen/sériový terminál



Provedení standardní



Provedení pro regulátory RT



Provedení univerzální

	00	10	20	30	40	50	60	70	80	90	A0	B0	C0	D0	E0	F0
00			0	1	2	3	4	5	6	7	8	9	.	/		
01		!	1	A	Q	a	q									
02		"	2	B	R	b	r									
03		#	3	C	S	c	s									
04		\$	4	D	T	d	t									
05		%	5	E	U	e	u									
06		&	6	F	V	f	v									
07		'	7	G	W	g	w									
08		<	8	H	X	h	x									
09		>	9	I	Y	i	y									
0A		*	:	J	Z	j	z									
0B		+	:	K	[	k	[									
0C		,	<	L	+	l	+									
0D		-	=	M	]	m	]									
0E		.	>	N	^	n	^									
0F		/	?/	O	_	o	_									

Znaková sada US + Azbuka (standardní)

	00	10	20	30	40	50	60	70	80	90	A0	B0	C0	D0	E0	F0
00			0	1	2	3	4	5	6	7	8	9	.	/		
01		!	1	A	Q	a	q									
02		"	2	B	R	b	r									
03		#	3	C	S	c	s									
04		\$	4	D	T	d	t									
05		%	5	E	U	e	u									
06		&	6	F	V	f	v									
07		'	7	G	W	g	w									
08		<	8	H	X	h	x									
09		>	9	I	Y	i	y									
0A		*	:	J	Z	j	z									
0B		+	:	K	[	k	[									
0C		,	<	L	+	l	+									
0D		-	=	M	]	m	]									
0E		.	>	N	^	n	^									
0F		/	?/	O	_	o	_									

Znaková sada US + Jap

Použitý řadič displeje (HD44780 kompatibilní) umožňuje uživatelsky naprogramovat znaky 00 ÷ 07H.

Otvor v panelu pro zástavbu CKDM-11/12, SKDM-11/12

